



CERTIFICATION RECORD

The company named below has been authorized by CSA International to represent the products listed in this record as "CSA Certified" and to affix the CSA Mark to these products according to the terms and conditions of the CSA Service Agreement and applicable CSA program requirements (including additional Markings).

File No: 105847_0_000
Class No: 3881 81 TOOLS Portable - Certified to US Standards

SUBMITTOR

4570094 Lee Yeong Industrial Co., Ltd.
No. 2, Kejia Rd., Douliu City,
Yunlin County, 64057
Taiwan

FACTORIES

4570094 Lee Yeong Industrial Co., Ltd.
No. 2, Kejia Rd., Douliu City,
Yunlin County, 64057
Taiwan

July 17, 2017 (Replaces: June 28, 2017)

TO THE REQUIREMENTS OF UL STD NO 45

- 4-3/8 inch tile cutter, Model LY-115, cord-connected, double-insulated, rated 120 V, 60 Hz, 11 A, 11000 rpm.
- 4 inch - 4-1/2 inch grinder, cord-connected, double-insulated, rated 120 V, 60 Hz, 6.5 A, 11000 rpm, Model LY-1008N; 5 inch grinder, Model LY-1008NF.
- Electric nibbler, cord-connected, double-insulated, Model LY-16, rated 120 V, 60 Hz, 4.2 A.
- 1/2 inch hammer drills, double-insulated, cord-connected, reversible, variable speed, Models LY-188 and 030426, rated 120 V, 60 Hz, 4.5 A, 3200 rpm.
- 1/4 inch screwdriver, double-insulated, cord-connected, reversible, variable speed, Model LY-0855, rated 120 V, 60 Hz, 5.0 A, 2800 rpm.
- 3/8 inch drills, double-insulated, cord-connected, reversible, variable speed, Models LY-0855N, 030420, rated 120 V, 60 Hz, 5.0 A, 2800 rpm.

TO THE REQUIREMENTS OF UL 60745-1-4th Edition

- Circular Saw, 320mm, cord-connected, double-insulated, Models CS320, SHD8320, MT320.
- Diamond Core Drill, cord connected, grounded Models DM6D, CD160D, CD6D, DM63D, HCD36, DM6P, CD160P, CD6P, DM63P, DMC6D, DMC160D, DMC63D, DMC6P, DMC160P, DMC63P.
- Wrap-around Tube Sander (Belt Sander)/ Drum Polisher (Polisher) , cord-connected, double-insulated Models WS760, 30-A 285,RSM760, 495050D,MR-760.1500, EDXE20, WS30, PS1001, PÁSOVEC 40V, 311-TK
- Tapper, cord-connected, double-insulated. Model T14; T16; PT14; ET14; T1416; PT1416; ET1416; 3860014; GSMPRO ; XLT TAPPER; GS18; T18 , rated 115Vac, 3.9A, 60Hz, FWD:280/REV:680 n0/min.