



3123569.50

EMC Test report for Rotary Bushhammer (polisher)

Model: BH92

Shanghai, date of issue: 2012-09-28

Author : Richie Tang

By order of Lee Yeong Industrial Co., Ltd. at Douliu City, Yunlin County, Taiwan

A handwritten signature in black ink that reads 'Richie Tang'.

A handwritten signature in black ink that reads 'sky zhang'.

author : Richie Tang

reviewed : Sky Zhang

B 24 pages 0 annexes (sec)

DEKRA Testing and Certification China Ltd. DOCUMENT

SH-F-PC4-005 v1.1

CONTENTS

		page
1	Conclusion.....	3
1.1	Model description	3
1.2	Environment	5
1.3	Classification	5
2	Summary	6
2.1	Applied standards.....	6
2.2	Overview of results	6
3	General Information.....	7
3.1	Product Information	7
3.2	Customer Information	7
3.3	Test data.....	8
3.4	Environmental conditions	8
4	Emission test results.....	9
4.1	Mains conducted disturbance voltage	9
4.2	Radiated emission	12
4.3	Harmonic currents	14
4.4	Voltage fluctuations (Flicker)	16
5	Immunity test results.....	17
5.1	Electrostatic discharge immunity	17
5.2	Electrical Fast Transient immunity.....	18
5.3	Surge transient immunity	19
5.4	RF Conducted immunity	20
5.5	Power supply interruptions and dips.....	21
6	Identification of the equipment under test.....	22

1 CONCLUSION

The equipment under test (EUT) does meet the essential requirements of the EMC Directive 2004/108/EC.

The tests described in this report do not result in the right to use any approval mark as conferred by DEKRA. As far as the tests were based on certain specifications, these are mentioned in the report.

The conclusion and results stated in this test report are based on a non-recurrent examination of sample(s) provided by the applicant.

1.1 Model description

The apparatus as supplied for the test is a Rotary Bushhammer (polisher), model BH92 intended for residential use. The EUT has electronic control circuit but no earth connection.



Figure 1 Overview



Figure 2 Overview



Figure 3 Internal view

The operating modes as stated in the user manual are on and off modes.

1.2 Environment

The requirements and standards apply to equipment intended for use in:

✓	Residential (domestic) environment
✓	Commercial and light-industrial environment
	Industrial environment
	Medical environment

1.3 Classification

The standard EN 55014-2 is subdivided in four categories. For each category, the specific immunity requirements are formulated.

	Category 1	Apparatus containing no electronic control circuitry
✓	Category 2	Apparatus containing electronic control circuitry with no internal clock or oscillator frequency higher than 15 MHz.
	Category 3	Battery powered apparatus containing electronic control circuitry with no internal clock higher than 15 MHz.
	Category 4	All other apparatus.

2 SUMMARY

This chapter presents an overview of standards and results. Refer to the next chapters for details of measured test results and applied test levels.

2.1 Applied standards

Standard	Year	Title
EN 55014-1	2006	Emission – Electrical motor-operated and thermal appliances for household and similar purposes, electrical tools and similar electrical apparatus
A1	2009	
A2	2011	
EN 55014-2	1997	Immunity - Household appliances, electric tools and similar
A1	2001	
A2	2008	
EN 61000-3-2	2006	Limits for harmonic currents emissions
A1	2009	
A2	2009	
EN 61000-3-3	2008	Limitation of voltage fluctuations and flicker

2.2 Overview of results

Emission tests	Result
Mains conducted disturbance voltage	PASS
Radiated emission	PASS
Harmonic current emission	PASS
Limitation of voltage fluctuations (flicker)	PASS

Immunity tests	Result
Electrostatic Discharges (ESD)	PASS
Electrical fast transient (EFT)	PASS
Surge transients	PASS
Conducted RF disturbances	PASS
Power supply voltage interruptions & dips	PASS

3 GENERAL INFORMATION

3.1 Product Information

Equipment under test	Rotary Bushhammer (polisher)
Trade mark	AGP
Tested Type	BH92
U nominal	220-240 Vac; 50-60 Hz
P rated	1200 W

3.2 Customer Information

Applicant/Manufacturer	Lee Yeong Industrial Co., Ltd.
Contact person	Ms. Diane Wu
Telephone	+886 5 551 8689
Telefax	+886 5 551 8635
Address	No.2, Kejia Road, Douliu City, Yunlin County 64057, Taiwan

Factory	Lee Yeong Industrial Co., Ltd.
Contact person	Ms. Diane Wu
Telephone	+886 5 551 8689
Telefax	+886 5 551 8635
Address	No.2, Kejia Road, Douliu City, Yunlin County 64057, Taiwan

3.3 Test data

Location	Global Certification Corp.
Address	No.146, Sec. 2, Xiangzhang Rd., Xizhi Dist., New Taipei City 221, Taiwan
Date	March 2012
Supervised by	Richie Tang

3.4 Environmental conditions

Tests have been performed in a controlled laboratory environment, where the environmental conditions are maintained within the applicable ranges.

Ambient temperature	15 °C – 35 °C
Relative Humidity air	30% - 60%

Measurement Uncertainty

Conducted Emission Expanded Uncertainty: $U = 3.38$ dB

Disturbance Power Expanded Uncertainty: $U = 3.92$ dB

4 EMISSION TEST RESULTS

4.1 Mains conducted disturbance voltage


Standard			EN 55014-1 (Tools)					
Frequency [MHz]			QP [dB(μV)]		AV [dB(μV)]			
0,15	–	0,35	66	–	59 *)	59	–	49 *)
0,35	–	5	59		49			
5	–	30	64		54			

*) Limits decreasing linearly with the logarithm of the frequency

	Rated power below 700 W	Limits as above
	Rated power between 700 and 1000 W	Limits +4 dB
✓	Rated power above 1000 W	Limits +10 dB

Port	AC mains
Test method	LISN
Mode	On mode with an artificial hand, no load


Line



	Read		Over	Limit		
Freq	Level	Level	Factor	Limit	Line	Remark

	MHz	dBuV	dBuV	dB	dB	dBuV
1	0.18	41.10	51.41	10.31	-15.28	66.69 Average
2	0.18	63.13	73.44	10.31	-0.94	74.38 Peak
3	0.21	41.20	51.50	10.30	-13.81	65.31 Average
4	0.21	60.54	70.84	10.30	-2.58	73.42 Peak
5	0.43	46.02	56.33	10.31	-12.67	69.00 Peak
6	1.42	45.42	55.82	10.40	-13.18	69.00 Peak
7	11.93	42.86	53.70	10.84	-20.30	74.00 Peak
8	16.57	42.08	53.07	10.99	-20.93	74.00 Peak

Neutral



	Read	Over Limit		Limit		Line Remark
	Freq	Level	Level	Factor	Limit	
	MHz	dBuV	dBuV	dB	dB	dBuV
1	0.15	40.19	50.48	10.29	-18.33	68.81 Average
2	0.15	61.01	71.30	10.29	-4.57	75.87 Peak
3	0.18	41.59	51.86	10.27	-15.14	67.00 Average
4	0.18	61.92	72.19	10.27	-2.41	74.60 Peak
5	0.21	41.30	51.55	10.25	-13.70	65.25 Average
6	0.21	62.52	72.77	10.25	-0.60	73.37 Peak
7	0.22	37.90	48.15	10.25	-16.29	64.44 Average
8	0.22	57.69	67.94	10.25	-4.86	72.80 Peak
9	1.41	29.40	39.75	10.35	-19.25	59.00 Average
10	1.41	49.73	60.08	10.35	-8.92	69.00 Peak
11	1.58	29.70	40.06	10.36	-18.94	59.00 Average
12	1.58	49.03	59.39	10.36	-9.61	69.00 Peak
13	12.52	44.80	55.61	10.81	-18.39	74.00 Peak
14	19.64	41.53	52.57	11.04	-21.43	74.00 Peak

No other significant emissions were recorded at the frequency range of interest employing the QP detector.

Refer to chapter 6 for the test set-up.

Conclusion:

PASS

4.2 Radiated emission

Standard	EN 55014-1	
Frequency [MHz]	QP [dB(pW)]	AV [dB(pW)]
30 – 300	45 – 55 *)	35 – 45 *)


*) Limits increasing linearly with the frequency

For tools the following limits apply to the AC Mains port:

	Rated power below 700 W	Limits as above
	Rated power between 700 and 1000 W	Limits +4 dB
✓	Rated power above 1000 W	Limits +10 dB

Port	AC Mains
Mode	On mode with no load

Results



	Read Freq	Read Level	Limit Level	Limit Factor	Over Line	Over Limit	Remark
	MHz	dBpW	dBpW		dB	dBpW	dB
1	32.29	31.74	32.37	0.63	55.33	-22.96	Peak
2	44.07	31.36	32.10	0.74	56.68	-24.58	Peak
3	71.14	29.85	30.85	1.00	58.76	-27.91	Peak
4	117.25	34.71	36.08	1.37	60.93	-24.85	Peak
5	156.72	29.42	31.02	1.60	62.19	-31.17	Peak
6	228.62	29.96	32.06	2.10	63.83	-31.77	Peak

No other significant emissions were measured at the frequency range of interest employing both the QP and AV detectors.

Refer to chapter 6 for the test set-up.

According to clause 4.1.2.3.2 (EN 55014-1):

Appliances are deemed to comply in the frequency range from 300 MHz to 1 000 MHz if both of the following conditions (1) and 2)) are fulfilled:

- 1) all emission readings from the equipment under test shall be lower than the applicable limits (Table 2a) reduced by the margin (Table 2b);
- 2) the maximum clock frequency shall be less than 30 MHz.

Conclusion:

PASS

4.3 Harmonic currents

Standard	EN 61000-3-2
Port	AC Mains supply
Rated power	1200 W
Mode	On mode

	Class A	All apparatus not classified as Class B, C or D
✓	Class B	Portable tools
	Class C	Lighting equipment
	Class D	Personal computers, television receivers

Results

Test completed, Result: PASSED

Order	Freq. [Hz]	Iavg [A]	Irms [A]	Irms% [%]	Irms%L [%]	Imax [A]	Imax%L [%]	Limit [A]	Status	Vrms [V]	Phase [deg]
1	60	1.5540	1.4911	71.516		1.6895				230.43	0.00
2	120	0.0330	0.0311	1.4930	2.8822	0.0366	3.3908	1.0800		0.2209	0.00
3	180	1.2557	1.2036	57.728	52.331	1.3464	58.541	2.3000		0.2454	0.00
4	240	0.0252	0.0238	1.1417	5.5357	0.0281	6.5293	0.4300		0.0491	0.00
5	300	0.7739	0.7501	35.978	65.800	0.8179	71.743	1.1400		0.1718	0.00
6	360	0.0144	0.0134	0.6440	4.4759	0.0165	5.4932	0.3000		0.0491	0.00
7	420	0.3247	0.3210	15.398	41.694	0.3345	43.438	0.7700		0.0491	0.00
8	480	0.0000	0.0061	0.2927	2.6537	0.0067	2.9191	0.2300		0.0245	0.00
9	540	0.0784	0.0812	3.8934	20.294	0.0818	20.447	0.4000		0.0982	0.00
10	600	0.0000	0.0037	0.1756	1.9903	0.0043	2.3220	0.1840		0.0245	0.00
11	660	0.0685	0.0745	3.5714	22.565	0.0751	22.749	0.3300		0.0736	0.00
12	720	0.0000	0.0055	0.2635	3.5825	0.0055	3.5825	0.1533		0.0245	0.00
13	780	0.0515	0.0549	2.6347	26.158	0.0555	26.449	0.2100		0.0245	0.00
14	840	0.0000	0.0061	0.2927	4.6440	0.0067	5.1084	0.1314		0.0245	0.00
15	900	0.0684	0.0659	3.1616	43.945	0.0714	47.607	0.1500		0.0982	0.00
16	960	0.0000	0.0067	0.3220	5.8381	0.0073	6.3689	0.1150		0.0245	0.00
17	1020	0.0647	0.0665	3.1909	50.266	0.0671	50.727	0.1324		0.0491	0.00
18	1080	0.0000	0.0061	0.2927	5.9708	0.0073	7.1650	0.1022		0.0245	0.00
19	1140	0.0417	0.0427	2.0492	36.079	0.0433	36.594	0.1184		0.0245	0.00
20	1200	0.0000	0.0061	0.2927	6.6343	0.0073	7.9611	0.0920		0.0000	0.00
21	1260	0.0425	0.0397	1.9028	37.028	0.0470	43.864	0.1071		0.0736	0.00

22	1320	0.0000	0.0055	0.2635	6.5679	0.0073	8.7572	0.0836	0.0245	0.00
23	1380	0.0378	0.0385	1.8443	39.307	0.0385	39.307	0.0978	0.0245	0.00
24	1440	0.0000	0.0049	0.2342	6.3689	0.0067	8.7572	0.0767	0.0000	0.00
25	1500	0.0236	0.0244	1.1710	27.127	0.0244	27.127	0.0900	0.0245	0.00
26	1560	0.0000	0.0049	0.2342	6.8996	0.0067	9.4870	0.0708	0.0000	0.00
27	1620	0.0240	0.0226	1.0831	27.100	0.0262	31.494	0.0833	0.0491	0.00
28	1680	0.0000	0.0049	0.2342	7.4304	0.0073	11.146	0.0657	0.0245	0.00
29	1740	0.0211	0.0220	1.0539	28.320	0.0226	29.107	0.0776	0.0245	0.00
30	1800	0.0000	0.0037	0.1756	5.9708	0.0073	11.942	0.0613	0.0000	0.00
31	1860	0.0149	0.0153	0.7319	21.023	0.0159	21.864	0.0726	0.0245	0.00
32	1920	0.0000	0.0037	0.1756	6.3689	0.0055	9.5533	0.0575	0.0000	0.00
33	1980	0.0172	0.0165	0.7904	24.170	0.0177	25.960	0.0682	0.0491	0.00
34	2040	0.0000	0.0043	0.2049	7.8948	0.0055	10.150	0.0541	0.0245	0.00
35	2100	0.0132	0.0159	0.7611	24.685	0.0159	24.685	0.0643	0.0245	0.00
36	2160	0.0000	0.0049	0.2342	9.5533	0.0073	14.330	0.0511	0.0000	0.00
37	2220	0.0000	0.0116	0.5562	19.070	0.0134	22.081	0.0608	0.0245	0.00
38	2280	0.0000	0.0043	0.2049	8.8236	0.0067	13.866	0.0484	0.0000	0.00
39	2340	0.0114	0.0128	0.6148	22.217	0.0134	23.275	0.0577	0.0491	0.00
40	2400	0.0000	0.0049	0.2342	10.615	0.0061	13.269	0.0460	0.0245	0.00

Urms = 230.5V Freq = 59.925 Range: 10 A
Irms = 2.085A Ipk = 5.571A cf = 2.672
P = 160.8W S = 480.6VA pf = 0.334
THDi = 70.1 % THDu = 0.20 %

Conclusion:

PASS

4.4 Voltage fluctuations (Flicker)

Standard	EN 61000-3-3
Port	AC Mains supply
Voltage	230 V _{AC}
Mode	On mode

Equipment intended to be connected to 230/400 V_{AC} 50 Hz supply systems may not produce voltage fluctuations in the supply systems due to variation of the input current above the limits as stated below.

P _{ST}	Not applicable*
P _{LT}	Not applicable*
dt > 3,3%	≤ 500 ms
d _C	≤ 3,3%
d _{MAX}	≤ 4%

Results

Relative voltage change characteristic dt	0,0 ms
Maximum voltage change d _{MAX}	1,143%
Relative Voltage change d _C	0,251%
Short term flicker P _{ST}	Not applicable*
Long term flicker P _{LT}	Not applicable*

In addition, this test was conducted in accordance with Annex B of EN 61000-3-3:2008.

* The EUT belongs to hand-held tools (portable tools without heating elements), according to EN 61000-3-3, clause A.9, P_{ST} and P_{LT} shall not be evaluated.

Conclusion:

PASS

5 IMMUNITY TEST RESULTS

5.1 Electrostatic discharge immunity

Electrostatic discharges (ESD) are the result of persons or objects that accumulate static electricity due to for instance walking on synthetic carpets. The ESD can influence the operation of equipment or damage its electronics, either by a direct discharge or indirectly by coupling or radiation. Both effects are simulated during the tests.

Requirements

Standard	EN 55014-2
Basic standard	EN 61000-4-2
Port	Enclosure
Performance criterion	B; During the test degradation is allowed. No change of operating state or stored data is allowed.
Air discharges	8 kV
Contact discharges	4 kV
Mode	On mode

Performed tests

Air discharges	✓	4 kV	✓	8 kV		15 kV		
Contact discharges	✓	2 kV	✓	4 kV		8 kV		
Via coupling planes	✓	Horizontal			✓	Vertical		
Polarity	✓	Positive			✓	Negative		
Set-up	✓	Table-top				Floor standing		
Ambient temperature	21 °C							
Relative Humidity air	48%							

Observations

During the test no loss of performance was observed. After the test the EUT functioned as intended. No unacceptable loss of performance was observed.

Conclusion:

PASS

5.2 Electrical Fast Transient immunity

The EFT immunity test simulates disturbances by bursts of very short transients caused for example by switching off loads such as an AC motor or bouncing relay contacts. The transients are likely to disturb electronics but less likely to cause damage.

Requirements

Standard	EN 55014-2		
Basic standard	EN 61000-4-4		
Performance criterion	B; During the test degradation is allowed. No change of operating state or stored data is allowed.		
Pulse characteristics	5/50 ns		
Peak Voltage; Port	1 kV; AC input power port		
Repetition frequency	✓	5 kHz	2,5 kHz

Performed tests

Tested Voltage; Port	1 kV; AC input power port		
Mode	On mode		
Injection method	✓	CDN	Capacitive clamp
Polarity	✓	Positive	✓ Negative
Set-up	✓	Table-top	Floor standing

Observations

During the test no loss of performance was observed. After the test the EUT functioned as intended. No unacceptable loss of performance was observed.

Conclusion:

PASS

5.3 Surge transient immunity

The surge transient immunity test simulates the surges that are caused by overvoltages due to indirect (induced) lightning transients. The pulse is a slow transient with high-energy contents and due to its long duration may cause damage to an unprotected EUT.

Requirements

Standard	EN 55014-2
Basic standard	EN 61000-4-5
Performance criterion	B; During the test degradation is allowed. No change of operating state or stored data is allowed.
Pulse characteristics	1,2/50 μ s
Peak Voltage; Port	1 kV; AC input power port (Line to line)

Performed tests

Tested Voltage; Port	1 kV; AC input power port (Line to line)		
Mode	On mode		
Polarity	✓	Positive	✓ Negative

Observations

During the test no loss of performance was observed. After the test the EUT functioned as intended. No unacceptable loss of performance was observed.

Conclusion:

PASS

5.4 RF Conducted immunity

During this test the immunity of the equipment for induced or conducted electromagnetic fields is checked. Fields generated by radio and other transmitters cause RF voltages in long cables like the mains network. This test reproduces these induced disturbing voltages by injecting them to the EUT via the cabling.

Requirements

Standard	EN 55014-2
Basic standard	EN 61000-4-6
Performance criterion	A; Operation as intended
Frequency range	0,15 – 230 MHz
Modulation	1 kHz – 80% AM
Test level; Port	3 V; AC input power port

Performed tests

Tested level; Port	3 V; AC input power port		
Mode	On mode		
Frequency range	0,15 – 230 MHz		
Dwell time	3 seconds		
Injection method	✓	CDN-M2	EM clamp

Observations

During the test no loss of performance was observed. After the test the EUT functioned as intended. No unacceptable loss of performance was observed.

Conclusion:

PASS

5.5 Power supply interruptions and dips

Requirements

Basic standard	EN 61000-4-11
Performance criterion	B; During the test degradation is allowed. No change of operating state or stored data is allowed. C; Temporary, self-recoverable loss of function is allowed.

Standard	EN 55014-2			
AC input power port			50 Hz	60 Hz
	C	$U_{NOM} - 30\%$	(25 periods)	(30 periods)
	C	$U_{NOM} - 60\%$	(10 periods)	(12 periods)
	C	$U_{NOM} - 100\%$	(0,5 period)	(0,5 period)

Performed tests

Tested voltage	AC input power port		
Mode	On mode		
AC input power port	50 Hz		60 Hz
	$U_{NOM} - 30\%$ (25 periods)		$U_{NOM} - 30\%$ (30 periods)
	$U_{NOM} - 60\%$ (10 periods)		$U_{NOM} - 60\%$ (12 periods)
	$U_{NOM} - 100\%$ (0,5 period)		$U_{NOM} - 100\%$ (0,5 period)

Observations

During the test no loss of performance was observed. After the test the EUT functioned as intended. No unacceptable loss of performance was observed.

Conclusion:

PASS

6 IDENTIFICATION OF THE EQUIPMENT UNDER TEST

The photograph shows the tested device.



Figure 4 Conducted Emission test setup



Figure 5 Disturbance power test setup



Figure 6 Harmonics & Flicker & Surge & DIPS test setup




Figure 7 ESD test setup



Figure 8 EFT test setup



Figure 9 Conducted RF disturbances test setup