



DME51D Dry Diamond Core Drill Motor

Jun. 2024

Internal & Confidential

AGP | DME51D Dry Diamond Core Drill Motor

AGP TAIWAN

Lee Yeong Industrial Co., Ltd.

No.2, Kejia Rd., Douliu City, 64057, Taiwan

Tel: 886-5-5518689 Fax: 886-5-5518635

AGP EUROPE BV

Evenbroekveld 16D, 9420 Erpe-Mere, Belgium Tel: +32 53 21 62 22 Fax: +32 53 83 88 20



Introduction Target group & Applications

DME51D Introduction

The DME51D is an essential tool for all electricians. It is a powerful single speed dry drilling motor featuring soft percussion and external dust collection for drilling highly abrasive materials. In conjunction with the CG125 wall chaser, it allows the operator to create fast, high quality, socket installations. Compared to traditional methods, it is a quantum improvement.

Target Group & Applications

This item has a quite specific application, being specially designed for drilling sockets for electricians, usually in the size 82 mm. Thus, it is optimized for this size and has the features needed for this task.





Sales Arguments





1 Dust Extractor Head
for use with banana slot
type socket bits. External
location keeps fine abrasive
dust away from the gearbox.



2 Switchable Soft Percussion keeps the diamond segments sharp for more efficient dry drilling. Can be turned off when not needed.



3 Side Handle
is inline with the spindle
for best control.



4 Tubular Spirit Level ensures accurate drilling angle.

External Extractor Combinations

AGP external dust extractor comes with a choice of thread forms. Its design makes it easy to mount or remove the core bit, and also to easily free up a blocked bit. The openable access door allows convenient access for your standard-type wrenches. No need to use special wrenches, which may not be available on the job site when you need them!


Wa Du

Watch How to Use

Dust Extractor Video







Technical Specification

Model	DME51D			
Power Input	1800 W			
Voltage	110-120 V~ 50-60 Hz			
	220-240 V~ 50-60 Hz			
No Load /Full Load Speed	3600 / 2160 min ⁻¹			
Percussion Frequency	56.000 b/min			
Arbor Thread	M16-2.0 or M18-2.5			
Capacity-Dry	102 mm (4")			
Dimensions (mm)	450 x 90 x 210 mm			
Neck Diameter	60 mm			
Net Weight	4.7 kg			



- 1 Side Handle
- 2 Lock Screw (Side Handle)
- 3 Tubular Spirit Level
- 4 Trigger Switch
- **5** Lock Button
- **6** Spindle

- Percussion Selector
- 8 Motor
- Power Supply Cable
- 10 Main Handle
- 11 Hammer Symbol (Percussion On)
- 12 No Hammer Symbol (Percussion Off)



Offer Content

Standard Accessories

- DME51D Dry Diamond Core Drill Motor
- 2 Soft-Grip Side Handle

Recommended Item

- 3 External Dust Extractor Head
- 4 Centering Pilots for bit lengths 85 mm or 65 mm
- 5 Vacuum Collector Pad (Small up to 75 mm, large up to 130 mm)





Comparison Table

Brand













Dry Socket Drilling w/ External
Dust Collector
(mostly for Electricians)













Model No.	DME51D	ESD 1801	BDB 822 AP	BDB 824 S	EHD 1500	DK116
Power Input	220-240 V: 1800 W	220-240 V: 1800 W	220-240 V: 1650 W	220-240 V: 2000 W	220-240 V: 1500 W	220-240 V: 1600 W
Capacity-dry	102 mm	90 mm	40 - 90 mm	40 - 82 mm	82 mm	82 mm
Spindle	M18-2.5 or M16-2.0	M18-2.5 (dust extractor is M16)	M18-2.5 (dust extractor is M16)	M16	M18-2.5 (dust extractor is M16)	M16
RPM (rated load)	2160 /min	0 - 2050 /min	1800 /min	2400 /min	0 - 2000 /min	1500 /min
Percussion Frequency	56 000 bpm	41 000 bpm	36 000 bpm	N/A	N/A	N/A
Switchable Percussion	YES	YES	YES	NO	NO	NO
Built-in Level	YES	NO	YES	YES	NO	YES
Blowcase	YES	YES	YES	YES	YES	YES
Anti-Vibration Side Handle	Optional 👛	NO	NO	NO	NO	NO
LED Load Indicator	NO	NO	YES	YES	YES	NO
Variable Speed Switch	NO	YES	NO	NO	YES	NO
Weight	4.7 kg	5.9 kg	4.98 kg	5.0 kg	3.9 kg	5.0 kg
Dust Collector Description	Choice of M16 or M18 thread (for banana slot type bits only). No limitation on length.	socket bits with banana	For M16 thread, short socket bits with banana slot vents. Also can use side slot socket bits with the optional bell-type dust extractor.	clet vents only	For M16 thread, short socket bits with banana slot vents only.	For M16 thread, short socket bits with banana slot vents only.
Dust Collector	Optional	Optional	Standard	Standard	Optional	Standard
Centering Aid	Spring-loaded centering pilot	Masonry drill bit	Spring-loaded centering pilot	Built-in spring-loaded centering pilot	Masonry drill bit	Built-in spring-loaded centering pilot integrated with motor
Conclusion	The AGP brings together all the drilling. The AGP external dus					g aid to allow optimal

Tool Dimensions (mm)

